Typ X, GAD, SD, Industry

Material supply in Milk-Run-Train

FEATURES

- stackable
- loading and unloading on both sides
- mesh cover
- swivelling drawbar
- virtual clutch and drawbar system

self-locking drawbar

foot protection



ergonomic handle on castor side

stackable

Typ X, GAD, SD, Industry

Material supply in Milk-Run-Train

dimensions outside l x w in mm:

- 1460 x 1060

effective surface l x w in mm:

- 1225 x 1025

loading capacity in kg:

- 1000

max. velocity in km/h:

- 6

max. towing capacity:

- 3000

technical data:

- hot-dip galvanised welded steel construction in stable X-shape
- ergonomic handle on castor side
- 50mm high feed-in aids at the corners
- mesh cover
- additional side reinforcement as support for the grating
- swivelling drawbar
- securing the drawbar against uncontrolled falling if the spring breaks
- virtual clutch anddrawbar system for optimum directional stability

serial running gear:

- 2 fixed castors and 2 castors with Extrathane running surface, 92° Shore A, crowned running surface, ø 160 mm
- castors with wheel and slewing ring locking device, wheel centre made of diecast aluminium
- all castors with ball bearings
- wheelguard on all 4 castors

optional:

- swivelling drawbar
- covers: - chequer plate - steel sheet - phenol resin board
- adjustment of use height
- central braking & locking device
- castors suitable for outdoor operation
- weather protection
- R6 + R6 plus - particularly manoeuvrable
- electrically conductive castors
- Antistatic strap
- DIN A5/A4 clipboard

FURTHER PRODUCTS

Typ X.1 Euro

Typ X, GAD, SD, Euro

Typ X.1, Industry

Typ X.2, Industry